

## **11,000 Altered Farm Rules for 2025**

### **Engine**

1. 466 ci with 2% allowances.
2. Intake hose on Turbo must be easily removable for inspection purposes.
3. Injection pump will be limited to nothing bigger than a A-pump.
4. Water Injection is allowed with no accelerants.
5. NO Intercoolers allowed.
6. Exhaust must exit at least 18" above the hood and have two 3/8 bolts through the pipe forming a cross to prevent parts from exiting the exhaust.
7. Must have a metal shroud around the fan. 360 degrees of 1/8 inch Metal. Electric fans are permitted.
8. Must run a steel flywheel. No cast flywheels allowed.
9. Side shields required.
10. No aftermarket transmissions are allowed.
11. Turbo must be 3x3 Smoothbore Box charger. Borgwarner Part # 177101 from Brian Wright at Wright's Performance (540) 974-7852

### **Tire & Wheel Limitations**

1. 20.8 x 38 or a 18.4 x 42 will be the maximum size tire allowed.
2. Top Cut Tires will be allowed. No alterations to front edge of bar.
3. Aluminum wheels are allowed on the front only.

### **Chassis and Hitch**

1. Maximum hitch height will be 20".
2. Minimum of 18" from center of rear to hitch point.

### **Safety**

1. Wheelie bars, must have 5x5 inch pad, no more than 10 inches from the ground (must be 3 inches from farthest point of rear tire to front of the pad)
2. A working air shut off must be installed to connect to the sled.
3. All tractors must be equipped with a fire extinguisher.
4. All tractors are subject to be teched at any event.