

Truck Outfitters 6300 Outlaw 4x4 Rules for 2026-2028

New Rules for 2026

1. **Weight change to 6300lbs.**
2. **All previous 6400 Pro Stock Trucks will abide by ALL previous 6400 rules in 2026 except for overall weight requirement of 6300lbs. This will be on a TRIAL BASIS FOR 2026 PULLING SEASON!**
3. **Must run a SQUARE bore intake carburetor flange.**

Engine Limitations

1. Must be naturally aspirated engine. No blowers, turbos or nitrous
 1. **Must run a SQUARE bore intake carburetor flange.**
 2. Must run single **4 barrel** carburetor with a square mounting flange. No rectangular shaped mounting flanges allowed.
 3. Dry sump oiling will be allowed
 4. Center of Engine cannot be further forward than the center of the front axle. (i.e. center of Carburetor or intake can't be further forward than the center of the front axle.)

Chassis, Body, and Powertrain

1. No power train parts over 1 ton allowed
2. No fiberglass body parts with the exception of the hood and tailgate.
3. Must have factory glass in all windows
4. Wheel base limited to 141" which is a short wheel base extended cab truck. All axles must be in the stock locations no matter which body style is used. If different manufacturer body is used the frame will be used to determine the correct stock location. (General appearance should have the wheels in the center of the wheel wells.)
5. There will be a maximum length of 195 inches from the furthest point of the weight frame to the center of the rear axle
6. Hydraulic steering is allowed.
7. Vertical exhaust is allowed
8. Must have a working back-up light that is actuated when truck is put in reverse.
9. Weight frames may not extend any further forward than 60" from the center of the front axle and must be less than 80" wide.
 1. Hitch must be rigid in all directions (No upward travel)
 2. Front pivot point of hitch can be no higher than 2 inches above the stock frame rails.
 3. Hitch must have at least a 3" round opening horizontal to the ground as a hook point.
10. We have adopted the hitch rules of the other organizations that run this class
 - a. Hitch height will be 26 inches.
 - b. No less than 27% of wheelbase from center of rear to hook point of hitch
 - c. Hitch mounting point must not be more than 2 inches above the frame

Tires and Wheels

1. Tires must be DOT approved and limited to 35" X 12.50" max tire size. (No cutting or grooving)
2. No dual wheels allowed.

Safety

1. Truck must be equipped with a blow proof bell housing or transmission shields / blankets.
2. Working kill switch with a 1" hole for a hook point at the rear of the truck,
3. All U-joints must be fully shielded and all drive shafts must have rigid loops to catch the shaft in the event of breakage.
4. All competitors must wear a helmet.